

Flow Meter (High Capacity) for BIGboy™



Batteries included.

IMPORTANT NOTICE

Use this meter for water only. Do not use to meter fuel or chemicals.

This meter is not legal for trade applications.

The meter is very sensitive to electrical “noise” and may not operate correctly if located near some electrical equipment.

CALIBRATION

This meter has a permanent factory calibration for measuring water. If installed and used correctly, inaccuracies of no greater than $\pm 5\%$ will be obtained.

INSTALLATION

This meter may be installed in-line either horizontally or vertically or at the end of the hose adjacent to the nozzle, if present. Installation to metal connections is not recommended. Install as follows:

1. If necessary, remove nozzle from hose.
2. Apply pipe sealant to all threaded connections.
3. Attach meter to hose with arrow on outlet port pointed in the direction of flow.
4. If necessary, attach nozzle to meter
5. Hand tighten the meter at the housing ends. Do not use a wrench or similar tools to tighten the meter housing. The plastic housing could be damaged.

OPERATION

Batch and Cumulative Totals

The meter maintains two totals. The batch total may be reset to measure flow during a single use. The cumulative total provides continuous measurement and may not be manually reset. The batch total is labeled as TTL1. The cumulative total is labeled TTL2.

When the cumulative total reaches a maximum reading of 9999, it will automatically reset to zero.

Press the DISPLAY button briefly to switch between the batch and cumulative total.

Activate the Meter

Turn the meter ON by starting water flow or briefly pressing the DISPLAY button. The meter will display the batch or cumulative total from last use.

Press DISPLAY briefly to display the batch total. Hold the DISPLAY button down for three seconds to reset the batch total to zero.

The meter is programmed to turn off automatically if not used for about one minute.

MAINTENANCE

Proper handling and care will extend the life and service of the meter.

Turbine Rotor

The meter is virtually maintenance-free. However, it is important the rotor moves freely. Keep the meter clean and free of contaminants.

If the rotor does not turn freely, apply a penetrating lubricant on the rotor, shaft, and bearings. Remove any debris or deposits from the rotor using a soft brush or small probe. Be careful not to damage the turbine rotor or supports.

CAUTION: Blowing compressed air through the turbine assembly could damage the rotor.



Flow Meter (High Capacity) for BIGboy™

Battery Replacement

The meter is powered by two AAA alkaline batteries which may be replaced while the meter is installed. When batteries are removed or lose power, the batch and cumulative totals reset to zero but the factory calibration is retained.

If the meter display becomes dim or blank, replace the batteries as follows:

1. Remove the four Phillips-head screws from the face of the meter and lift the faceplate from the turbine.
2. Remove the old batteries and clean any corrosion from the terminals.
3. Install new batteries. Make sure the positive post is in the correct position.
4. When the batteries are replaced, the faceplate will power ON. Check the display to ensure normal functions have resumed before assembling again.
5. Re-seat batteries, if necessary, and position the faceplate on the turbine housing. To avoid moisture damage, make sure the O-ring is fully seated. Tighten the four screws on the faceplate.

SPECIFICATIONS

Model:	01N31GM
Unit of Measure:	Gallons
Flow Rate:	3 to 30 GPM
Working Pressure:	150 PSIG
Operating Temperature:	+14°F to +130°F
Storage Temperature:	-40°F to +158°F
Threads:	1 inch NPT

Model:	01N31LM
Unit of Measure:	Liters
Flow Rate:	10 to 100 LPM
Working Pressure:	10.3 bar
Operating Temperature:	-10°C to +54°C
Storage Temperature:	-40°F to +70°C
Threads:	1 inch NPT

Model:	01N21LM
Unit of Measure:	Liters
Flow Rate:	10 to 100 LPM
Working Pressure:	10.3 bar
Operating Temperature:	-10°C to +54°C
Storage Temperature:	-40°F to +70°C
Threads:	1 inch ISO

WARRANTY

A One Year Warranty comes with each unit against manufacturer's defects. This does not include clogging due to lack of regular maintenance or excessive sediment and/or contaminants in water. This warranty also excludes damage to units caused by using the unit outside of the specified parameters. Do not operate your filter unit if incoming pressure exceeds 80 psi or there is problem with water hammer spikes. If unsure of water pressure, check with a pressure gauge available at your dealer or hardware store. Install the optional pressure regulator if inlet pressure is above 80 psi.

Do not contact your dealer or distributor for warranty issues.

Contact HydroLogic directly.

For Tech Assistance **call 888.426.5644 x106** or **email info@hydrologicsystems.com**

370 Encinal Street, Suite 150 | Santa Cruz, California | www.hydrologicsystems.com